

**FAG N1006-K-M1-SP参数**

|        |               |       |       |             |
|--------|---------------|-------|-------|-------------|
| 尺寸     | d             | 30    | mm    | -           |
|        | D             | 55    | mm    | -           |
|        | B             | 13    | mm    | -           |
|        | $D_{a\ max}$  | 50    | mm    | -           |
|        | $D_{b\ min}$  | 50    | mm    | -           |
|        | $d_1$         | 38.7  | mm    | -           |
|        | $d_{a\ min}$  | 33.2  | mm    | -           |
|        | E             | 48.5  | mm    | -           |
|        | $r_{a\ max}$  | 1     | mm    | -           |
|        | $r_{min}$     | 1     | mm    | -           |
|        |               | s     | 1.5   | mm          |
| 重量     | m             | 145   | g     | 质量          |
| 基本额定载荷 | $C_r$         | 19400 | N     | 基本额定动载荷，径向  |
|        | $C_{0r}$      | 19300 | N     | 基本额定静载荷，径向  |
| 极限转速   | $n_{G\ Fett}$ | 20000 | r/min | 脂润滑时的极限转速   |
|        | $n_{G\ Öl}$   | 24000 | r/min | 最少油润滑时的极限转速 |
| 疲劳极限载荷 | $C_{ur}$      | 2850  | N     | 疲劳极限载荷，径向   |

**FAG N1006-K-M1-SP图片**



