

FAG NJ217-E-TVP2 + HJ217-E参数

尺寸	B_2	12.5	mm	-
	D_1	131.5	mm	-
	$D_{a\ max}$	139	mm	-
	d_1	107.5	mm	-
	$d_{a\ max}$	99	mm	-
	$d_{a\ min}$	96	mm	-
	$d_{c\ min}$	110	mm	-
	E	136.5	mm	-
	F	100.5	mm	-
	$r_{l\ min}$	2	mm	-
	$r_{a\ max}$	2	mm	-
	$r_{al\ max}$	2	mm	-
	r_{min}	2	mm	-
	s	0.8	mm	距离中心位置的轴向偏移
说明		HJ217-E		型号, L 型圈
重量	m	1950	g	质量
	m_1	247	g	质量, L 型圈
基本额定载荷	C_r	194000	N	基本额定动载荷, 径向
	C_{0r}	194000	N	基本额定静载荷, 径向
极限转速	n_G	5600	r/min	极限转速
参考转速	n_B	4050	r/min	参考速度
疲劳极限载荷	C_{ur}	33500	N	疲劳极限载荷, 径向
尺寸	d	85	mm	-
	D	150	mm	-
	B	28	mm	-
	B_1	8	mm	-

FAG NJ217-E-TVP2 + HJ217-E图片



