

FAG 30306-A参数

尺寸	$r_{a \max}$	1.5	mm	-	
	$r_{b \max}$	1.5	mm	-	
重量	m	445	g	质量	
基本额定载荷	C_r	60000	N	基本额定动载荷, 径向	
	C_{0r}	61000	N	基本额定静载荷, 径向	
计算系数	e	0.31		-	
	Y	1.9		-	
	Y_0	1.05		-	
疲劳极限载荷	C_{ur}	6900	N	疲劳极限载荷, 径向	
尺寸	T	20.75	mm	-	
	a	15	mm	-	
	B	19	mm	-	
	C	16	mm	-	
	$C_{a \min}$	3	mm	-	
	$C_{b \min}$	4.5	mm	-	
	$D_{a \max}$	65	mm	-	
	$D_{a \min}$	62	mm	-	
	$D_{b \min}$	66	mm	-	
	d_1	49.3	mm	-	
	$d_{a \max}$	40	mm	-	
	$d_{b \min}$	37	mm	-	
	$r_{1, 2 \min}$	1.5	mm	-	
	$r_{3, 4 \min}$	1.5	mm	-	
	d	30	mm	-	
	D	72	mm	-	
	极限转速	n_G	11000	r/min	极限转速
	参考转速	n_B	7200	r/min	参考速度

FAG 30306-A图片

