

### FAG HCB7002-E-T-P4S参数

|        |                    |        |       |             |
|--------|--------------------|--------|-------|-------------|
| 尺寸     | d                  | 15     | mm    | -           |
|        | D                  | 32     | mm    | -           |
|        | B                  | 9      | mm    | -           |
|        | a                  | 10     | mm    | -           |
|        | $D_a$ H12          | 29     | mm    | -           |
|        | $d_a$ h12          | 19     | mm    | -           |
|        | $r_{1\ min}$       | 0.3    | mm    | -           |
|        | $r_{a\ max}$       | 0.3    | mm    | -           |
|        | $r_{al\ max}$      | 0.1    | mm    | -           |
|        | $r_{\min}$         | 0.3    | mm    | -           |
|        | 重量                 | m      | 27    | g           |
| 基本额定载荷 | $C_r$              | 5900   | N     | 基本额定动载荷，径向  |
|        | $C_{0r}$           | 1610   | N     | 基本额定静载荷，径向  |
| 极限转速   | $n_{G\ Fett}$      | 63000  | r/min | 脂润滑时的极限转速   |
|        | $n_{G\ \ddot{o}l}$ | 100000 | r/min | 最少油润滑时的极限转速 |
| 疲劳极限载荷 | $C_{ur}$           | 168    | N     | 疲劳极限载荷，径向   |

### FAG HCB7002-E-T-P4S图片



