

FAG 32228-A参数

| | | | | |
|--------|-----------------|---------|-------|--------------------------|
| 尺寸 | $C_{b \min}$ | 13.5 | mm | - |
| | $D_{a \max}$ | 236 | mm | - |
| | $D_{a \min}$ | 210 | mm | - |
| | $D_{b \min}$ | 238 | mm | - |
| | d_1 | 193.5 | mm | - |
| | $d_{a \max}$ | 159 | mm | - |
| | $d_{b \min}$ | 154 | mm | - |
| | $r_{1, 2 \min}$ | 4 | mm | - |
| | $r_{3, 4 \min}$ | 3 | mm | - |
| | $r_{a \max}$ | 4 | mm | - |
| | $r_{b \max}$ | 3 | mm | - |
| 重量 | m | 14000 | g | 质量 |
| 基本额定载荷 | C_r | 640000 | N | 基本额定动载荷, 径向 |
| | C_{0r} | 990000 | N | 基本额定静载荷, 径向 |
| 计算系数 | e | 0.44 | | - |
| | Y | 1.38 | | - |
| | Y_0 | 0.76 | | - |
| 疲劳极限载荷 | C_{ur} | 120000 | N | 疲劳极限载荷, 径向 |
| 极限转速 | n_G | 2700 | r/min | 极限转速 |
| 参考转速 | n_B | 1740 | r/min | 参考速度 |
| 说明 | | T4FD140 | | 根据 DIN ISO 355 的 对应型号 |
| 尺寸 | d | 140 | mm | - |
| | D | 250 | mm | - |
| | T | 71.75 | mm | - |
| | a | 60 | mm | - |
| | B | 68 | mm | - |
| | C | 58 | mm | - |

FAG 32228-A图片

