

FAG B71944-E-T-P4S参数

| | | | | |
|--------|----------------------|--------|-------|-------------|
| 重量 | m | 6580 | g | 质量 |
| 基本额定载荷 | C_r | 212000 | N | 基本额定动载荷, 径向 |
| | C_{0r} | 192000 | N | 基本额定静载荷, 径向 |
| 系数 | f_0 | 16.5 | | - |
| 极限转速 | $n_{G \text{ Fett}}$ | 3800 | r/min | 脂润滑时的极限转速 |
| | $n_{G \text{ Öl}}$ | 6000 | r/min | 最少油润滑时的极限转速 |
| 疲劳极限载荷 | C_{ur} | 12200 | N | 疲劳极限载荷, 径向 |
| 尺寸 | d | 220 | mm | - |
| | D | 300 | mm | - |
| | B | 38 | mm | - |
| | a | 80 | mm | - |
| | $D_a \text{ H12}$ | 286 | mm | - |
| | $d_a \text{ h12}$ | 234 | mm | - |
| | $r_{1 \text{ min}}$ | 1.1 | mm | - |
| | $r_{a \text{ max}}$ | 1 | mm | - |
| | r_{min} | 2.1 | mm | - |
| | $r_{a1 \text{ max}}$ | 1 | mm | - |

FAG B71944-E-T-P4S图片



