

FAG 33108参数

尺寸	d	40	mm	-	
	D	75	mm	-	
	T	26	mm	-	
	a	18	mm	-	
	B	26	mm	-	
	C	20.5	mm	-	
	C <sub>a min</sub>	4	mm	-	
	C <sub>b min</sub>	5.5	mm	-	
	D <sub>a max</sub>	68	mm	-	
	D <sub>a min</sub>	65	mm	-	
	D <sub>b min</sub>	71	mm	-	
	d <sub>1</sub>	58.7	mm	-	
	d <sub>a max</sub>	47	mm	-	
	d <sub>b min</sub>	47	mm	-	
	r <sub>1, 2 min</sub>	1.5	mm	-	
	r <sub>3, 4 min</sub>	1.5	mm	-	
	r <sub>a max</sub>	1.5	mm	-	
	r <sub>b max</sub>	1.5	mm	-	
	重量	m	541	g	质量
	基本额定载荷	C <sub>r</sub>	79000	N	基本额定动载荷, 径向
C <sub>0r</sub>		103000	N	基本额定静载荷, 径向	
计算系数	e	0.36		-	
	Y	1.69		-	
	Y <sub>0</sub>	0.93		-	
疲劳极限载荷	C <sub>ur</sub>	12800	N	疲劳极限载荷, 径向	
极限转速	n <sub>G</sub>	9500	r/min	极限转速	
参考转速	n <sub>B</sub>	5500	r/min	参考速度	

FAG 33108图片

