

FAG 33217参数

尺寸	$r_{b \max}$	2	mm	-
重量	m	3580	g	质量
基本额定载荷	C_r	295000	N	基本额定动载荷，径向
	C_{0r}	435000	N	基本额定静载荷，径向
计算系数	e	0.42		-
	Y	1.43		-
	Y_0	0.79		-
疲劳极限载荷	C_{ur}	53000	N	疲劳极限载荷，径向
极限转速	n_G	4500	r/min	极限转速
参考转速	n_B	3050	r/min	参考速度
说明		T3EE085		根据 DIN ISO 355 的 对应型号
尺寸	a	37	mm	-
	B	49	mm	-
	C	37	mm	-
	$C_{a \min}$	7	mm	-
	$C_{b \min}$	12	mm	-
	$D_{a \max}$	140	mm	-
	$D_{a \min}$	128	mm	-
	$D_{b \min}$	144	mm	-
	d_1	117.8	mm	-
	$d_{a \max}$	95	mm	-
	$d_{b \min}$	95	mm	-
	$r_{1, 2 \min}$	2.5	mm	-
	$r_{3, 4 \min}$	2	mm	-
	$r_{a \max}$	2.5	mm	-
	d	85	mm	-
D	150	mm	-	

FAG 33217图片

