

## FAG 33205参数

尺寸	d	25	mm	-	
	D	52	mm	-	
	T	22	mm	-	
	a	14	mm	-	
	B	22	mm	-	
	C	18	mm	-	
	$C_{a \text{ min}}$	4	mm	-	
	$C_{b \text{ min}}$	4	mm	-	
	$D_{a \text{ max}}$	46	mm	-	
	$D_{a \text{ min}}$	43	mm	-	
	$D_{b \text{ min}}$	49	mm	-	
	$d_1$	39.6	mm	-	
	$d_{a \text{ max}}$	30	mm	-	
	$d_{b \text{ min}}$	31	mm	-	
	$r_{1, 2 \text{ min}}$	1	mm	-	
	$r_{3, 4 \text{ min}}$	1	mm	-	
	$r_{a \text{ max}}$	1	mm	-	
	$r_{b \text{ max}}$	1	mm	-	
	重量	m	214	g	质量
	基本额定载荷	$C_r$	48500	N	基本额定动载荷，径向
$C_{0r}$		58000	N	基本额定静载荷，径向	
计算系数	e	0.35		-	
	Y	1.71		-	
	$Y_0$	0.94		-	
疲劳极限载荷	$C_{ur}$	6900	N	疲劳极限载荷，径向	
极限转速	$n_G$	14200	r/min	极限转速	
参考转速	$n_B$	8200	r/min	参考速度	

FAG 33205图片

