

FAG 22322-E1参数

| | | | | |
|--------|--------------------|---------|-------|------------|
| 尺寸 | d | 110 | mm | - |
| | D | 240 | mm | - |
| | B | 80 | mm | - |
| | D ₁ | 204.9 | mm | - |
| | D _{a max} | 226 | mm | - |
| | d ₂ | 143.1 | mm | - |
| | d _{a min} | 124 | mm | - |
| | d _s | 8 | mm | - |
| | n _s | 15 | mm | - |
| | r _{a max} | 2.5 | mm | - |
| | r _{min} | 3 | mm | - |
| | 重量 | m | 17700 | g |
| 基本额定载荷 | C _r | 950000 | N | 基本额定动载荷，径向 |
| 计算系数 | e | 0.33 | | - |
| | Y ₁ | 2.07 | | - |
| | Y ₂ | 3.09 | | - |
| 基本额定载荷 | C _{0r} | 1070000 | N | 基本额定静载荷，径向 |
| 计算系数 | Y ₀ | 2.03 | | - |
| 极限转速 | n _G | 3000 | r/min | 极限转速 |
| 参考转速 | n _B | 2240 | r/min | 参考速度 |
| 疲劳极限载荷 | C _{ur} | 91000 | N | 疲劳极限载荷，径向 |

FAG 22322-E1图片



参考资料:<http://www.sozhou.com/p/2f6a351b.html>