

### FAG NU2209-E-TVP2参数

尺寸	d	45	mm	-
	D	85	mm	-
	B	23	mm	-
	D <sub>1</sub>	73.3	mm	-
	D <sub>a max</sub>	78	mm	-
	d <sub>a max</sub>	54	mm	-
	d <sub>a min</sub>	52	mm	-
	d <sub>b min</sub>	57	mm	-
	E	76.5	mm	-
	F	54.5	mm	-
	r <sub>1 min</sub>	1.1	mm	-
	r <sub>a max</sub>	1	mm	-
	r <sub>al max</sub>	1	mm	-
	r <sub>min</sub>	1.1	mm	-
	s	1.5	mm	距离中心位置的轴向偏移
重量	m	532	g	质量
基本额定载荷	C <sub>r</sub>	87000	N	基本额定动载荷，径向
	C <sub>0r</sub>	82000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	10200	r/min	极限转速
参考转速	n <sub>B</sub>	5800	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	13900	N	疲劳极限载荷，径向

### FAG NU2209-E-TVP2图片



参考资料:<http://www.sozhou.com/p/37705a05.html>

