

**FAG B71913-E-T-P4S参数**

|        |                      |       |       |             |
|--------|----------------------|-------|-------|-------------|
| 尺寸     | $r_{l \text{ min}}$  | 1     | mm    | -           |
|        | $r_{a \text{ max}}$  | 0.6   | mm    | -           |
|        | $r_{al \text{ max}}$ | 0.6   | mm    | -           |
|        | $r_{\text{min}}$     | 1     | mm    | -           |
| 重量     | m                    | 199   | g     | 质量          |
| 基本额定载荷 | $C_r$                | 23700 | N     | 基本额定动载荷，径向  |
|        | $C_{0r}$             | 16000 | N     | 基本额定静载荷，径向  |
| 系数     | $f_0$                | 16.5  |       | -           |
| 极限转速   | $n_{G \text{ Fett}}$ | 13000 | r/min | 脂润滑时的极限转速   |
|        | $n_{G \text{ Öl}}$   | 20000 | r/min | 最少油润滑时的极限转速 |
| 疲劳极限载荷 | $C_{ur}$             | 1640  | N     | 疲劳极限载荷，径向   |
| 尺寸     | d                    | 65    | mm    | -           |
|        | D                    | 90    | mm    | -           |
|        | B                    | 13    | mm    | -           |
|        | a                    | 25    | mm    | -           |
|        | $D_a \text{ H12}$    | 85.5  | mm    | -           |
|        | $d_a \text{ h12}$    | 70    | mm    | -           |

**FAG B71913-E-T-P4S图片**



