

FAG 23280-B-K-MB + H3280参数

尺寸	d_{1H}	380	mm	-
	D	720	mm	-
	B	256	mm	-
	$B_{a \min}$	15	mm	-
	c	62	mm	-
	c_1	81	mm	-
	D_1	609.8	mm	-
	$D_{a \max}$	694	mm	-
	D_m	520	mm	-
	d	400	mm	-
	$d_{a \max}$	473	mm	-
	$d_{b \min}$	427	mm	-
	d_s	12.5	mm	-
	l	328	mm	-
	n_s	23.5	mm	-
	$r_{a \max}$	5	mm	-
	r_{\min}	6	mm	-
	说明		H3280	
重量	m	442000	g	质量
	m_1	82100	g	质量, 紧定套
基本额定载荷	C_r	5700000	N	基本额定动载荷, 径向
计算系数	e	0.38		-
	Y_1	1.78		-
	Y_2	2.65		-
基本额定载荷	C_{0r}	10800000	N	基本额定静载荷, 径向
计算系数	Y_0	1.74		-
极限转速	n_G	810	r/min	极限转速

参考转速	n_B	375	r/min	参考速度
疲劳极限载荷	C_{ur}	820000	N	疲劳极限载荷，径向

FAG 23280-B-K-MB + H3280图片

