

NSK 52414参数

| | | | | |
|--------|------|--------|-------|------|
| 外形尺寸 | SD | 70 | mm | 外径 |
| | D | 150 | mm | 宽度 |
| | T1 | 107 | mm | - |
| | T5 | 114.2 | mm | - |
| | T7 | 125 | mm | - |
| | SR | 2.0 | mm | (最小) |
| | SR1 | 1.0 | mm | (最小) |
| 基本额定载荷 | CAN | 252000 | N | 动载荷 |
| | COAN | 555000 | N | 静载荷 |
| | CA | 25700 | kgf | 动载荷 |
| | COA | 56500 | kgf | 静载荷 |
| 极限转速 | GRE | 1000 | 1/min | 脂润滑 |
| | OIL | 1500 | 1/min | 油润滑 |
| 尺寸 | SD3 | 150.0 | mm | - |
| | D1 | 73 | mm | - |
| | D2 | 110 | mm | - |
| | D3 | 155 | mm | - |
| | T2 | 65.5 | mm | - |
| | T6 | 69.1 | mm | - |
| | T8 | 74.5 | mm | - |
| | B | 24 | mm | - |
| | SB | 19.5 | mm | - |
| | A1 | 28.5 | mm | - |
| | R | 112 | mm | - |
| 安装尺寸 | DA | 110 | mm | (最大) |
| | SRA | 2.0 | mm | (最大) |
| | SRB | 1.0 | mm | (最大) |
| 重量 | MASS | 8990 | g | 重量 |
| 型号 | 型号 | 52414 | | - |
| 外形尺寸 | SD2 | 55 | mm | 内径 |

NSK 52414图片

