

## FAG 33208参数

尺寸	d	40	mm	-	
	D	80	mm	-	
	T	32	mm	-	
	a	21	mm	-	
	B	32	mm	-	
	C	25	mm	-	
	$C_{a \text{ min}}$	5	mm	-	
	$C_{b \text{ min}}$	7	mm	-	
	$D_{a \text{ max}}$	73	mm	-	
	$D_{a \text{ min}}$	67	mm	-	
	$D_{b \text{ min}}$	76	mm	-	
	$d_1$	60.1	mm	-	
	$d_{a \text{ max}}$	47	mm	-	
	$d_{b \text{ min}}$	47	mm	-	
	$r_{1, 2 \text{ min}}$	1.5	mm	-	
	$r_{3, 4 \text{ min}}$	1.5	mm	-	
	$r_{a \text{ max}}$	1.5	mm	-	
	$r_{b \text{ max}}$	1.5	mm	-	
	重量	m	741	g	质量
	基本额定载荷	$C_r$	105000	N	基本额定动载荷，径向
$C_{0r}$		134000	N	基本额定静载荷，径向	
计算系数	e	0.36		-	
	Y	1.68		-	
	$Y_0$	0.92		-	
疲劳极限载荷	$C_{ur}$	16600	N	疲劳极限载荷，径向	
极限转速	$n_G$	9000	r/min	极限转速	
参考转速	$n_B$	5700	r/min	参考速度	

FAG 33208图片

