

## NACHI 6021ZNR参数

|           |         |        |       |      |
|-----------|---------|--------|-------|------|
| 外形尺寸      | d       | 105    | mm    | 内径   |
|           | D       | 160    | mm    | 外径   |
|           | B       | 26     | mm    | 宽度   |
|           | r       | 2~3.5  | mm    | 轴向   |
|           | r       | 2~5    | mm    | 轴向   |
|           | r1      | 0.5~   | mm    | 径向   |
|           | r1      | 0.5~   | mm    | 径向   |
| 止动槽和止动环尺寸 | D1      | 155.22 | mm    | (最大) |
|           | a       | 3.71   | mm    | (最大) |
|           | D2      | 169.7  | mm    | (最大) |
|           | f       | 2.82   | mm    | (最大) |
| 安装尺寸      | da(min) | 113    | mm    | (最小) |
|           | Da(max) | 152    | mm    | (最大) |
|           | Dx(min) | 172    | mm    | (最小) |
|           | ra(max) | 2      | mm    | (最大) |
|           | Cy(max) | 6.1    | mm    | (最大) |
| 基本额定载荷    | Cr      | 72500  | N     | 动载荷  |
|           | Cor     | 65500  | N     | 静载荷  |
| 极限速度      | Grease  | 4000   | r/min | 脂润滑  |
|           | Oil     | 4800   | r/min | 油润滑  |

## NACHI 6021ZNR图片

参考资料:<http://www.sozhou.com/p/6b5c829e.html>

