

FAG NJ2309-E-TVP2参数

尺寸	$r_{a \max}$	1.5	mm	-	
	$r_{al \max}$	1.5	mm	-	
	r_{\min}	1.5	mm	-	
	s	2.5	mm	距离中心位置的轴向偏移	
重量	m	1330	g	质量	
基本额定载荷	C_r	163000	N	基本额定动载荷, 径向	
	C_{0r}	154000	N	基本额定静载荷, 径向	
极限转速	n_G	8500	r/min	极限转速	
参考转速	n_B	5400	r/min	参考速度	
尺寸	d	45	mm	-	
	D	100	mm	-	
	B	36	mm	-	
	B_1	7	mm	-	
	B_2	13	mm	-	
	D_1	84.1	mm	-	
	$D_{a \max}$	91	mm	-	
	d_1	64.4	mm	-	
	$d_{a \max}$	57	mm	-	
	$d_{a \min}$	54	mm	-	
	$d_{c \min}$	66	mm	-	
	F	58.5	mm	-	
	$r_{l \min}$	1.5	mm	-	
	疲劳极限载荷	C_{ur}	28000	N	疲劳极限载荷, 径向

FAG NJ2309-E-TVP2图片





参考资料:<http://www.sozhou.com/p/7133d068.html>