

FAG BND3080-H-C-T-AL-S参数

| | | | | |
|----|----------------|----------|----|---------|
| 尺寸 | d ₁ | 380 | mm | - |
| | a | 1060 | mm | - |
| | h ₁ | 720 | mm | - |
| | g ₁ | 310 | mm | - |
| | b | 320 | mm | - |
| | c | 110 | mm | - |
| | D | 600 | mm | - |
| | d _c | 400 | mm | - |
| | g | 175 | mm | - |
| | g ₄ | 145 | mm | - |
| | h | 360 | mm | - |
| | k | 7 | mm | - |
| | m | 900 | mm | - |
| | n | 200 | mm | - |
| | s | M48 | | - |
| 说明 | s ₂ | M20 | | - |
| 尺寸 | t | 650 | mm | - |
| | u | 56 | mm | - |
| | v | 75 | mm | - |
| 说明 | s ₂ | 8 | | 数量 |
| | | 23080K | | 型号, 轴承 |
| 其他 | | H3080-HG | | 质量, 紧定套 |
| 重量 | m ₁ | 400000 | g | 质量, 轴承座 |
| 说明 | | BND3080 | | 型号, 轴承座 |

FAG BND3080-H-C-T-AL-S图片



参考资料:<http://www.sozhou.com/p/735da1e2.html>

