

FAG 32009-XA参数

| | | | | | |
|-----------------|-----------------------|----------------|-------|-------------|-------------|
| 尺寸 | d | 45 | mm | - | |
| | D | 75 | mm | - | |
| | T | 20 | mm | - | |
| | a | 17 | mm | - | |
| | B | 20 | mm | - | |
| | C | 15.5 | mm | - | |
| | C _{a min} | 4 | mm | - | |
| | C _{b min} | 4.5 | mm | - | |
| | D _{a max} | 69 | mm | - | |
| | D _{a min} | 67 | mm | - | |
| | D _{b min} | 72 | mm | - | |
| | d ₁ | 62 | mm | - | |
| | d _{a max} | 51 | mm | - | |
| | d _{b min} | 51 | mm | - | |
| | r _{1, 2 min} | 1 | mm | - | |
| | r _{3, 4 min} | 1 | mm | - | |
| | r _{a max} | 1 | mm | - | |
| | r _{b max} | 1 | mm | - | |
| | 重量 | m | 354 | g | 质量 |
| | 基本额定载荷 | C _r | 61000 | N | 基本额定动载荷, 径向 |
| C _{0r} | | 86000 | N | 基本额定静载荷, 径向 | |
| 计算系数 | e | 0.39 | | - | |
| | Y | 1.53 | | - | |
| | Y ₀ | 0.84 | | - | |
| 疲劳极限载荷 | C _{ur} | 10200 | N | 疲劳极限载荷, 径向 | |
| 极限转速 | n _G | 9400 | r/min | 极限转速 | |
| 参考转速 | n _B | 5500 | r/min | 参考速度 | |

FAG 32009-XA图片

