

### FAG 294/500-E-MB参数

尺寸	d	500	mm	-
	D	870	mm	-
	T	224	mm	-
	A	290	mm	-
	D <sub>1</sub>	654	mm	-
	D <sub>a max</sub>	765	mm	-
	D <sub>b min</sub>	886	mm	-
	d <sub>1</sub>	790	mm	-
	d <sub>a min</sub>	670	mm	-
	d <sub>b max</sub>	542	mm	-
	r <sub>a max</sub>	8	mm	-
	r <sub>min</sub>	9.5	mm	-
	T <sub>1</sub>	107	mm	-
	T <sub>2</sub>	81	mm	-
	T <sub>3</sub>	142	mm	-
	T <sub>4</sub>	160	mm	-
	重量	m	519300	g
基本额定载荷	C <sub>a</sub>	9300000	N	基本额定动载荷, 轴向
	C <sub>0a</sub>	37000000	N	基本额定静载荷, 轴向
极限转速	n <sub>G</sub>	530	r/min	极限转速
参考转速	n <sub>B</sub>	340	r/min	参考速度
疲劳极限载荷	C <sub>ua</sub>	1910000	N	疲劳极限载荷, 轴向

### FAG 294/500-E-MB图片



参考资料:<http://www.sozhou.com/p/7ee4bff5.html>