

FAG BND3276-H-C-T-AL-S参数

| | | | | |
|----|-------|----------|----|---------|
| 尺寸 | g_4 | 244 | mm | - |
| | h | 425 | mm | - |
| | k | 5 | mm | - |
| | m | 1100 | mm | - |
| | n | 225 | mm | - |
| | s | M64 | | - |
| 说明 | s_2 | M30 | | - |
| 尺寸 | t | 745 | mm | - |
| | u | 72 | mm | - |
| | v | 90 | mm | - |
| 说明 | s_2 | 8 | | 数量 |
| | | 23276K | | 型号, 轴承 |
| 其他 | | H3276-HG | | 质量, 紧定套 |
| 重量 | m_1 | 1100000 | g | 质量, 轴承座 |
| 说明 | | BND3276 | | 型号, 轴承座 |
| 尺寸 | d_1 | 360 | mm | - |
| | a | 1350 | mm | - |
| | h_1 | 860 | mm | - |
| | g_1 | 489 | mm | - |
| | b | 405 | mm | - |
| | c | 135 | mm | - |
| | D | 680 | mm | - |
| | d_c | 384 | mm | - |
| | g | 295 | mm | - |

FAG BND3276-H-C-T-AL-S图片



参考资料:<http://www.sozhou.com/p/88cc66be.html>

