

### FAG 22234-E1-K参数

尺寸	d	170	mm	-
	D	310	mm	-
	B	86	mm	-
	D <sub>1</sub>	275.4	mm	-
	D <sub>a max</sub>	293	mm	-
	d <sub>2</sub>	199.8	mm	-
	d <sub>a min</sub>	187	mm	-
	d <sub>s</sub>	9.5	mm	-
	n <sub>s</sub>	17.7	mm	-
	r <sub>a max</sub>	3	mm	-
	r <sub>min</sub>	4	mm	-
	重量	m	27100	g
基本额定载荷	C <sub>r</sub>	1320000	N	基本额定动载荷，径向
尺寸	e	0.26		-
计算系数	Y <sub>1</sub>	2.6		-
	Y <sub>2</sub>	3.87		-
基本额定载荷	C <sub>0r</sub>	1570000	N	基本额定静载荷，径向
计算系数	Y <sub>0</sub>	2.54		-
极限转速	n <sub>G</sub>	2550	r/min	极限转速
参考转速	n <sub>B</sub>	1830	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	139000	N	疲劳极限载荷，径向

### FAG 22234-E1-K图片



参考资料:<http://www.sozhou.com/p/9203440c.html>