

**FAG 32952参数**

尺寸	d	260	mm	-	
	D	360	mm	-	
	T	63.5	mm	-	
	a	70	mm	-	
	B	63.5	mm	-	
	C	48	mm	-	
	C <sub>a min</sub>	11	mm	-	
	C <sub>b min</sub>	15.5	mm	-	
	D <sub>a max</sub>	348	mm	-	
	D <sub>a min</sub>	328	mm	-	
	D <sub>b min</sub>	347	mm	-	
	d <sub>1</sub>	309	mm	-	
	d <sub>a max</sub>	279	mm	-	
	d <sub>b min</sub>	272	mm	-	
	r <sub>1, 2 min</sub>	3	mm	-	
	r <sub>3, 4 min</sub>	2.5	mm	-	
	r <sub>a max</sub>	3	mm	-	
	r <sub>b max</sub>	2.5	mm	-	
	重量	m	18700	g	质量
	基本额定载荷	C <sub>r</sub>	750000	N	基本额定动载荷, 径向
C <sub>0r</sub>		1500000	N	基本额定静载荷, 径向	
计算系数	e	0.41		-	
	Y	1.48		-	
	Y <sub>0</sub>	0.81		-	
疲劳极限载荷	C <sub>ur</sub>	161000	N	疲劳极限载荷, 径向	
极限转速	n <sub>G</sub>	1780	r/min	极限转速	
参考转速	n <sub>B</sub>	990	r/min	参考速度	

FAG 32952图片

