

### NACHI 7340B参数

|        |          |        |       |      |
|--------|----------|--------|-------|------|
| 外形尺寸   | d        | 200    | mm    | 内径   |
|        | D        | 420    | mm    | 外径   |
|        | B        | 80     | mm    | 宽度   |
|        | r        | 5~8    | mm    | 径向   |
|        | r        | 5~10   | mm    | 径向   |
|        | r1       | 2~3.5  | mm    | 径向   |
|        | r1       | 2~5    | mm    | 径向   |
|        | 载荷中心     | a      | 90.1  | mm   |
| 安装尺寸   | da1(min) | 222    | mm    | (最小) |
|        | da2(min) | 210    | mm    | (最小) |
|        | Da1(max) | 398    | mm    | (最大) |
|        | Da2(max) | 410    | mm    | (最大) |
|        | ra(max)  | 4      | mm    | (最大) |
|        | ra1(max) | 2      | mm    | (最大) |
| 重量     | Mass     | 53700  | g     | 重量   |
| 基本额定载荷 | Cr       | 445000 | N     | 动载荷  |
|        | Cor      | 620000 | N     | 静载荷  |
| 极限速度   | Grease   | 1200   | r/min | 脂润滑  |
|        | Oil      | 1700   | r/min | 油润滑  |

### NACHI 7340B图片

参考资料:<http://www.sozhou.com/p/9f8f1cf4.html>

