

**FAG 33216参数**

尺寸	d	80	mm	-	
	D	140	mm	-	
	T	46	mm	-	
	a	35	mm	-	
	B	46	mm	-	
	C	35	mm	-	
	C <sub>a min</sub>	7	mm	-	
	C <sub>b min</sub>	11	mm	-	
	D <sub>a max</sub>	130	mm	-	
	D <sub>a min</sub>	119	mm	-	
	D <sub>b min</sub>	135	mm	-	
	d <sub>1</sub>	111.8	mm	-	
	d <sub>a max</sub>	89	mm	-	
	d <sub>b min</sub>	90	mm	-	
	r <sub>1, 2 min</sub>	2.5	mm	-	
	r <sub>3, 4 min</sub>	2	mm	-	
	r <sub>a max</sub>	2.5	mm	-	
	r <sub>b max</sub>	2	mm	-	
	重量	m	2930	g	质量
	基本额定载荷	C <sub>r</sub>	250000	N	基本额定动载荷, 径向
C <sub>0r</sub>		380000	N	基本额定静载荷, 径向	
计算系数	e	0.43		-	
	Y	1.41		-	
	Y <sub>0</sub>	0.78		-	
疲劳极限载荷	C <sub>ur</sub>	47000	N	疲劳极限载荷, 径向	
极限转速	n <sub>G</sub>	4800	r/min	极限转速	
参考转速	n <sub>B</sub>	3200	r/min	参考速度	

FAG 33216图片

