

### FAG 7211-B-TVP参数

尺寸	d	55	mm	-
	D	100	mm	-
	B	21	mm	-
	a	43	mm	-
	D <sub>1</sub>	83	mm	-
	D <sub>a max</sub>	91	mm	-
	D <sub>b max</sub>	94.4	mm	-
	d <sub>1</sub>	72.6	mm	-
	d <sub>a min</sub>	64	mm	-
	r <sub>1 min</sub>	1	mm	-
	r <sub>a max</sub>	1.5	mm	-
	r <sub>a1 max</sub>	1	mm	-
	r <sub>min</sub>	1.5	mm	-
	重量	m	604	g
基本额定载荷	C <sub>r</sub>	49000	N	基本额定动载荷，径向
计算系数	e	1.14		-
	X	0.35		-
	Y	0.57		-
	Y <sub>0</sub>	0.26		-
基本额定载荷	C <sub>0r</sub>	38500	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	8300	r/min	极限转速
参考转速	n <sub>B</sub>	6800	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	2600	N	疲劳极限载荷，径向

### FAG 7211-B-TVP图片



参考资料: <http://www.sozhou.com/p/a9581a32.html>