

IKO NUCF 30-2R参数

| | | | | | |
|----------|--------|------------|-------|----------|---|
| 杆端直径 | STDRT | 30 | mm | 杆端直径 | |
| 型号 | ORDER | NUCF 30-2R | | 型号 | |
| 重量 | MASS | 1970 | g | 重量 | |
| 主要尺寸 | D | 90 | mm | - | |
| | C | 35 | mm | - | |
| | SD1 | 30 | mm | - | |
| | G | M30x1.5 | | 螺纹规格 | |
| | G1 | 32 | mm | 螺纹尺寸 | |
| | B | 37.0 | mm | - | |
| | B1 | 100.0 | mm | - | |
| | B2 | 63.0 | mm | - | |
| | B3 | 15 | mm | - | |
| | C1 | 1.0 | mm | - | |
| | SG1 | 8 | mm | - | |
| | SG2 | 4 | mm | - | |
| | 安装尺寸 | SF | 45 | mm | - |
| | 最大拧紧扭矩 | TRQ | 438.0 | N. m | - |
| 基本额定载荷 | CR | 90300 | N | 动载荷 | |
| | COR | 121000 | N | 静载荷 | |
| 最大静态容许负荷 | FMAX | 98300 | N | 最大静态容许负荷 | |

IKO NUCF 30-2R图片

参考资料:<http://www.sozhou.com/p/aaa45e83.html>

