

NACHI 6013N参数

| | | | | |
|-----------|----------|---------|-------|------|
| 外形尺寸 | d | 65 | mm | 内径 |
| | D | 100 | mm | 外径 |
| | B | 18 | mm | 宽度 |
| | r | 1.1~2 | mm | 轴向 |
| | r | 1.1~3.5 | mm | 轴向 |
| | r1 | 0.5~ | mm | 径向 |
| | r1 | 0.5~ | mm | 径向 |
| 止动槽和止动环尺寸 | D1 | 96.8 | mm | (最大) |
| | a | 2.87 | mm | (最大) |
| | b | 2.7 | mm | (最小) |
| | D2 | 106.5 | mm | (最大) |
| | f | 2.46 | mm | (最大) |
| 安装尺寸 | da (min) | 71 | mm | (最小) |
| | Da (max) | 94 | mm | (最大) |
| | Dx (min) | 108 | mm | (最小) |
| | ra (max) | 1 | mm | (最大) |
| | Cy (max) | 5 | mm | (最大) |
| 基本额定载荷 | Cr | 30500 | N | 动载荷 |
| | Cor | 25200 | N | 静载荷 |
| 极限速度 | Grease | 6700 | r/min | 脂润滑 |
| | Oil | 8000 | r/min | 油润滑 |

NACHI 6013N图片

参考资料:<http://www.sozhou.com/p/c31e025a.html>

