

FAG B71940-C-T-P4S参数

| | | | | |
|--------|---------------------|--------|-------|-------------|
| 基本额定载荷 | C_r | 210000 | N | 基本额定动载荷，径向 |
| | C_{0r} | 179000 | N | 基本额定静载荷，径向 |
| 系数 | f_0 | 16.3 | | - |
| 极限转速 | $n_{G\text{ Fett}}$ | 4500 | r/min | 脂润滑时的极限转速 |
| | $n_{G\text{ Öl}}$ | 7000 | r/min | 最少油润滑时的极限转速 |
| 疲劳极限载荷 | C_{ur} | 11900 | N | 疲劳极限载荷，径向 |
| 尺寸 | d | 200 | mm | - |
| | D | 280 | mm | - |
| | B | 38 | mm | - |
| | a | 51 | mm | - |
| | $D_a\text{ H12}$ | 266 | mm | - |
| | $d_a\text{ h12}$ | 214 | mm | - |
| | $r_{l\text{ min}}$ | 1.1 | mm | - |
| | $r_{a\text{ max}}$ | 1 | mm | - |
| | $r_{al\text{ max}}$ | 1 | mm | - |
| | r_{min} | 2.1 | mm | - |
| 重量 | m | 6050 | g | 质量 |

FAG B71940-C-T-P4S图片



