

### FAG 22236-E1-K参数

尺寸	d	180	mm	-
	D	320	mm	-
	B	86	mm	-
	D <sub>1</sub>	285.9	mm	-
	D <sub>a max</sub>	303	mm	-
	d <sub>2</sub>	211.3	mm	-
	d <sub>a min</sub>	197	mm	-
	d <sub>s</sub>	9.5	mm	-
	n <sub>s</sub>	17.7	mm	-
	r <sub>a max</sub>	3	mm	-
	r <sub>min</sub>	4	mm	-
	重量	m	28500	g
基本额定载荷	C <sub>r</sub>	1360000	N	基本额定动载荷，径向
尺寸	e	0.25		-
计算系数	Y <sub>1</sub>	2.71		-
	Y <sub>2</sub>	4.04		-
基本额定载荷	C <sub>0r</sub>	1680000	N	基本额定静载荷，径向
计算系数	Y <sub>0</sub>	2.65		-
极限转速	n <sub>G</sub>	2470	r/min	极限转速
参考转速	n <sub>B</sub>	1710	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	148000	N	疲劳极限载荷，径向

### FAG 22236-E1-K图片



参考资料:<http://www.sozhou.com/p/caa04029.html>