

FAG JKOS040参数

尺寸	$r_{a \max}$	1	mm	-
	$r_1, r_{2 \min}^2$	1	mm	-
	u	0.03	mm	变化量 $\Delta D_n = +0,05$ mm
重量	m	300	g	大多数, 非脂润滑
说明		BR68		型号, 弹性挡圈
基本额定载荷	C_r	53000	N	基本额定动载荷, 径向
	C_{0r}	71000	N	基本额定静载荷, 径向
计算系数	e	0.37		-
	Y	1.6		-
	Y_0	0.88		-
疲劳极限载荷	C_{ur}	8300	N	疲劳极限载荷, 径向
极限转速	$n_{G \text{ Fett}}$	3200	r/min	脂润滑时的极限转速
承载力	F_{BR}	12900	N	止动环的承载能力 与 尖角处连接
说明		10600	N	轴承对的最大轴向安装 夹紧力 也提供注脂量达95%的 轴承; 型号: JKOS040-J14
尺寸	d	40	mm	-
	D	68	mm	-
	B	21	mm	-
	a	15.9	mm	-
	C	20.5	mm	-
	D_1	64.4	mm	-
	D_n	69.5	mm	槽的公称尺寸 变化量 $\Delta D_n = +0,19$ mm
	d_1	53.8	mm	-
	$d_{a \max}$	46	mm	-
	$d_{b \min}$	46	mm	-

FAG JKOS040图片



