

FAG 21308-E1-K参数

| | | | | |
|--------|--------------|--------|-------|-------------|
| 极限转速 | n_G | 9800 | r/min | 极限转速 |
| 参考转速 | n_B | 6100 | r/min | 参考速度 |
| 疲劳极限载荷 | C_{ur} | 14300 | N | 疲劳极限载荷, 径向 |
| 尺寸 | d | 40 | mm | - |
| | D | 90 | mm | - |
| | B | 23 | mm | - |
| | D_1 | 80.8 | mm | - |
| | $D_{a\ max}$ | 81 | mm | - |
| | d_2 | 59.9 | mm | - |
| | $d_{a\ min}$ | 49 | mm | - |
| | d_s | 3.2 | mm | - |
| | n_s | 4.8 | mm | - |
| | $r_{a\ max}$ | 1.5 | mm | - |
| | r_{min} | 1.5 | mm | - |
| | 重量 | m | 702 | g |
| 基本额定载荷 | C_r | 109000 | N | 基本额定动载荷, 径向 |
| 计算系数 | e | 0.23 | | - |
| | Y_1 | 2.95 | | - |
| | Y_2 | 4.4 | | - |
| 基本额定载荷 | C_{0r} | 107000 | N | 基本额定静载荷, 径向 |
| 计算系数 | Y_0 | 2.89 | | - |

FAG 21308-E1-K图片



参考资料:<http://www.sozhou.com/p/eba3c387.html>