

NSK 52240XM参数

| | | | | |
|--------|------|---------|-------|------|
| 型号 | 型号 | 52240XM | | - |
| 外形尺寸 | SD2 | 170 | mm | 内径 |
| | SD | 200 | mm | 外径 |
| | D | 280 | mm | 宽度 |
| | T1 | 109 | mm | - |
| | T5 | 115.6 | mm | - |
| | T7 | 133 | mm | - |
| | SR | 2.0 | mm | (最小) |
| | SR1 | 2.0 | mm | (最小) |
| 基本额定载荷 | CAN | 315000 | N | 动载荷 |
| | COAN | 1110000 | N | 静载荷 |
| | CA | 32500 | kgf | 动载荷 |
| | COA | 113000 | kgf | 静载荷 |
| 极限转速 | GRE | 710 | 1/min | 脂润滑 |
| | OIL | 1000 | 1/min | 油润滑 |
| 尺寸 | SD3 | 279.0 | mm | - |
| | D1 | 204 | mm | - |
| | D2 | 240 | mm | - |
| | D3 | 290 | mm | - |
| | T2 | 66.5 | mm | - |
| | T6 | 69.8 | mm | - |
| | T8 | 78.5 | mm | - |
| | B | 24 | mm | - |
| | SB | 23.0 | mm | - |
| | A1 | 120.5 | mm | - |
| | R | 225 | mm | - |
| 安装尺寸 | DA | 240 | mm | (最大) |
| | SRA | 2.0 | mm | (最大) |
| | SRB | 2.0 | mm | (最大) |
| 重量 | MASS | 23100 | g | 重量 |

NSK 52240XM图片



参考资料:<http://www.sozhou.com/p/f8ad0ef0.html>

