

## INA NUKRE90参数

尺寸	D	90	mm	-	
	d <sub>e</sub>	35	mm	偏心套 公差:h9	
	B	100	mm	-	
	B <sub>1 max</sub>	37	mm	-	
	B <sub>2</sub>	63	mm	-	
	B <sub>3</sub>	15	mm	-	
	B <sub>e</sub>	29	mm	偏心套	
	C	35	mm	-	
	C <sub>1</sub>	1	mm	-	
	d <sub>1</sub>	30	mm	公差:h7	
	d <sub>2</sub>	47	mm	-	
	d <sub>3</sub>	4	mm	-	
	e	1.5	mm	偏心套	
	G	M30x1.5		-	
	I <sub>G</sub>	32	mm	-	
	r <sub>min</sub>	1.1	mm	-	
	W	14	mm	内六角槽的公称尺寸	
	重量	m	2020	g	质量
	锁紧力矩	M <sub>A</sub>	450	Nm	螺母的锁紧力矩
	基本额定载荷	C <sub>r w</sub>	78000	N	滚轮的有效额定动载荷 (径向)
C <sub>0r w</sub>		123000	N	滚轮的有效额定静载荷 (径向)	
F <sub>r per</sub>		76000	N	许可动态径向载荷	
F <sub>0r per</sub>		123000	N	许可静态径向载荷	
疲劳极限载荷	C <sub>ur w</sub>	16700	N	疲劳极限载荷	
极限转速	n <sub>D G</sub>	1800	r/min	转速 (脂润滑下连续运转)	

